

Sub C

This is a continuation of reissue application serial no. 08/861,457 filed on May 22, 1997, which has issued as U.S. Patent No. RE37,867. Application serial no. 09/824,736, filed on April 4, 2001, is also a continuation of reissue application serial no. 08/861,457. Application serial no. 09/871,813, filed on June 4, 2001, is also a continuation of reissue application serial no. 08/861,457. Application serial no. 09/956,806, filed on September 21, 2001, is also a continuation of reissue application serial no. 08/861,457.

Please replace the paragraph beginning column 3, line 31 with the following:

Fig. 1d [11d] is a vertical cross section of an overshot-type tool used in case 1.
1, 371, 173

IN THE CLAIMS:

Please cancel claims 8-10 and 14 and amend claims 11 and 13 as follows:

- 6 11. (Amended) A method of sealing the intersection between a first borehole and a second borehole extending from said first borehole comprising the steps of:
- running into the first borehole an assembly comprising a housing and a tubular member within said housing, said housing having a window and said tubular member including a flange at an uphole end thereof, said flange being of larger dimension than said window;
- maintaining said tubular member substantially within said housing during run in; and
- aligning said window of said housing with a position where the second borehole is to be formed and moving said tubular member from the run in position to a deployed position wherein a portion of said tubular member extends through said window and outward of said housing and wherein said flange is mated against the periphery of said window;
- drilling the second borehole through the window of the housing.
- 9 12. The method of claim 11 wherein said flange includes an elastomeric sealing element.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

(17)

B